


Coiled Tubing BOP Stack

Reference standards: API 16A, GB/T 20174, API 16ST

Npmbsar _nnjga_`ggrw8 Qsgr\_`jc dmp amgj rs`gle mncp\_rgmI\* c cargtcjw npctclrgle `jmumsr _aagbclrq _lb
_a fgc tgle q_dc amI qrsargmI ,

Product Features

- ? rwnga_j amgjcb rs`gle ucjj amI rpmj bctgac glajsbcq\_@MN\_ lb \_qrpgnncp `mv,
- Bg_k crcp p_ lecl 1 /-6 +5 /- /4 * npcqqspc p_ lecl 0. . . nqg+/3. . . nqg,
- Rfc qrpgnncp `mv _bmnrq _ qgbc+mncIgle bmmpp bcqgeI* u fgaf k_ icq gr c_qw _lb
amI tclgcIrrm pcnj_ac rfc cjk kcl rctcl sl bcp amgj rs`gle mncp_rgmI ,
- Gr _bmnrq _bs_ j awjgl bcp qrsarspc* u fgaf sqcq ucjj npcqqspc rm _qqgqr qc_jgle* ugrf
pcjg_`jc qc_jgle* jmIe qcptgac jgdc* _lb jm u amI rpmj npcqqspc,
- Rfc @MN gq cosgnncb ugrf _`jgl b p\_ k \_qqc k`jw* _qfc_p_ k _qqc k`jw* _qjgn rwnc
p_ k _qqc k`jw\* \_lb \_ngnc p\_ k \_qqc k`jw,
- Rfc qjgn rwnc p_ k _qqc k`jw \_bmnrq \_pcnj\_ac\_`jc qrsarspc bcqgeI* _lb rfc slgosc
rmmr f bcqgeI pcbsacq b_ k _ec rm rfc amgjcb rs`gle,



15000psi

K_vg k s k npcqqspc

7 1/16"

K_vg k s k bg_k crcp

NACE MR0175

Qsjdsp pcqqr_ lac Jctcj

Application locations: Northeast China, Ordos and other regions, Southeast Asia.

Technical Parameters

Lm kgI_j bg_k crcp	1 /- /4 1 /-6 2 /- /4 3 /-6 5 /- /4
P_rcb umpigle npcqqspc	1. . . nqg 3. . . nqg / . . . nqg /3. . . nqg
Rc k ncp_rspc P_rgI eq dmp Kcr_jjga K_rcpq_jq	R+0. -13.
Rc k ncp_rspc P_rgI eq dmp LmI k cr_jjga Qc_jgle K_rcpq_jq	P_ k @MN Fgef cqr @ED
Qsjdsp pcqqr_ lac Jctcj	L?AC KP. /53
Qrpgnncp `mv	Qglejc* Bs_j
Amgjcb rs`gle @MN	Qglejc P_ k* Bms`jc P_ k* Os_b @MN,